

Card Printers

Card Printer P110i



General Features

- > Print speed: 30 sec/ card full-color, single-sided
- > 16-character LCD display
- > USB communication
- > Card feeder capacity: 100 cards
- > CardSense™ - single card feed (optional)
- > 3-track HiCo/LoCo magnetic encoder, available in stripe up or stripe down (optional)
- > i-Series Printers require the use of TrueColours™ i-Series Ribbons for full color printing

i Series



**Card
Printer
Solutions**

Zebra's most affordable single-sided color printer

Reliable, compact and easy to use, the P110i is Zebra's most affordable color card printer. The Zebra P110i is ideal for lower volume applications such as :

- > Access control cards
- > Employee ID cards
- > Memberchip cards
- > Loyalty cards and gift cards
- > Student ID's

Zebra P110i advantages

Versatile:

small footprint and light weight for use in a variety of locations, prints single-sided color or monochrome

Easy to use:

User-friendly USB plug-and-play setup, simple printhead replacement, blue touch points indicate user features

Innovative patent-pending technology:

Easy-to-replace Load-N-Go™ ribbon cartridge with integrated card cleaning roller, automatic color optimization and driver configuration, ribbon image counter and ribbon -low notification

All About Cards - Kompetenz rund um die Karte



Printer



Software



Cards



Card
Service



Card
Accessories



Card
Systems

Specifications

Card Printer P110 *i*



General Specifications

- Integrated card feeder
- Load-N-Go™ drop-in ribbon cartridge
- 16-character LCD display
- Windows® drivers: 2000, XP, Server 2003; Vista, Windows 7
- Two year printer warranty
- Two year (unlimited passes) original printhead warranty

Printing

- Color dye sublimation or monochrome thermal transfer printing
- 30 seconds per card full-color, single-sided
- 300 dpi print resolution

Bar Codes

- Code 39, Code 128 B & C with & without check digit
- 2 of 5 & 2 of 5 Interleaved
- UPC-A, EAN 8 & EAN 13
- PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- TrueType-Fonts via Windows drivers

Card Specifications

- Material: PVC, PVC Composite
- Card width/ length: ISO CR-80-ISO 7810, 54 x 86 mm
- Magnetic stripe: ISO 7811
- SmartCard: ISO 7816
- Card thickness: 0,76 mm
- Card feeder capacity: 100 cards (0,76mm)
- Card output hopper capacity: 45 cards (0,76mm)

Ribbon Specifications

- Load-N-Go™ ribbon cartridge with integrated card cleaning roller
- i-Series ribbon information technology
- YMCKO: 200 card sides/ cartridge
- Monochrome: 1.000 card sides/ cartridge in black, blue, red, green, gold and silver; 850 card sides/ cartridge in white



Communication Interface

- USB 1.1 (USB 2.0 compatible) cable included
- Optional built-in 10/100 Ethernet

Dimensions

- Width: 201 mm
- Depth: 328 mm
- Height: 216 mm
- Weight: 4,3 kg

Electrical

- 110/240 Volts AC, 50/60 Hz (auto switching)
- FCC Class A, CE, UL and CUL approved

Environmental

- Operating temperature: 60° F to 86° F, 15°C to 30°C
- Operating humidity: 20% to 65% non-condensing
- Storage temperature: 23° F to 158° F, -5°C to 70°C
- Storage relative humidity: 20% to 70% non condensing
- Ventilation: free air

Options

- Magnetic encoder (for 0,76 mm cards only), 3-track, HiCo/LoCo
- CardSense™ single card feed mode
- Built-in 10/100 Ethernet

