

VALUE

P120i



Advanced Design Delivers the World's First Dual-sided, Compact Card Printer at an Unprecedented Price

The P120i's versatility and affordability make this printer the smart choice for savvy buyers. From IDs to access control cards to gift cards, Zebra's P120i delivers big ideas at a small price.

Use the P120i card printer for:

- » Employee ID and Access cards
- » Student and Faculty ID's
- » Membership cards
- » Personalized Loyalty and Gift cards

Zebra P120i Advantages

Versatile: Print single-sided or dual-sided; Monochrome or full-color; Automatic card-feed or CardSense™ single cardfeed.

Easy-to-Use: Small; Lightweight; Reliable; 16-Character LCD display; Blue touch-points; Translucent card-cover; Toolless printhead replacement.

Economical: Most-affordable dual-sided printer.

Innovative Patent-Pending Technology: Compact design based on integrated card feeder-and-flipper; Gateless-feeding mechanism automatically handles various card thicknesses and eliminates the need for manual adjustment; Easy-to-replace Load-N-Go™ ribbon cartridge with integrated cardcleaning roller.

Key Features

- » 30 Sec/Card Full-Color, Single-Sided Print Speed
- » 35 Sec/Card Full-Color, Dual-Sided Print Speed
- » 16-digit LCD Display
- » USB- Communication
- » 100 Card-Capacity Feeder
- » CardSense™ Single Card-Feed (Optional)
- » 3 Track Magnetic Encoder (Optional)

*i*series



**Card
Printer
Solutions**

All About
Cards

P120i Product Specifications



TRUE
Colours
CARD PRINTER RIBBON

General Specifications

- » Integrated feeder-and-flipper
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-digit LCD display
- » Windows® drivers for 2000 and XP
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 30 seconds per card full-color single-sided (YMCKO)
- » 35 seconds per card full-color dual-sided (YMCKOK)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite, Adhesive backed
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 45 cards (30 mil)

Ribbon Specifications

- » Load-N-Go™ ribbon cartridge with integrated cardcleaning roller
- » i Series technology
- » YMCKO: 200 cards/cartridge
- » YMCKOK: 165 cards/cartridge
- » Monochrome: 1000 cards/cartridge in black, blue, or white

Communications Interface

- » USB 1.1 (cable included)

Mechanical

- » Width: 7.9 in (201mm)
- » Depth: 12.9 in (328 mm)
- » Height: 8.5 in (216 mm)
- » Weight: 9.5 lbs (4.3 kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 16MB image memory standard
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- » CardSense™ single-feed kit
- » Starter Kit (200 - 30 mil PVC cards and 1 YMCKOK ribbon)
- » Cleaning Kit (4 print engine and 4 feeder cleaning cards)

www.allaboutcards.biz

* for optimum printer performance use Genuine Zebra Supplies